

200 H.O.

HIGH OUTPUT (H.O.)

Engine Model	E200LH E200LHO E200XH E200XHC
Engine Type	V6 74° E-TEC D.I.
Bore x Stroke mm (in)	3.854 x 3.000 (98 x 76)
Displacement cc (cu in) L	2441 (210) 3.4 L
Gear Ratio (shaft length) ¹	1.85:1
Full Throttle RPM Range	5400-6000 RPM
Weight in KG (lbs) ²	244 (539)
Starting ¹	Electric
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output ³	133 Amps Total 50 net Dedicated 14 amps @ idle
Steering	Integrated Hydraulic
Trim Method	Trim & Tilt
Trim Range	-6 to 15
Tilt Range	81 deg
Shaft Length mm (in)	508 (20") 635 (25")
Lubrication	Multi-point Targeted Oiling
Oil Tank Capacity	Onboard 7.6 L (2) - Optional 37.9, 11.4, 6.8 L (10, 3, 1.8)
Recommended Oil	Evinrude Johnson XD-100 Oil
Recommended Fuel	87 Octane
Warranty	5-Year, Non Declining ⁵
Emissions Compliance	EPA 2013/CARB 3 STAR/EU 2006/EU 2016
Mounting Centers cm (in.)	Minimum 66 (26)
Steering Angle	32 deg from center, both directions
Integrated Features ¹	Hydraulic Steering Power Steering ⁴ On-Engine 2 gal Oil Tank



¹ May vary based on engine model number.

² Weight refers to the actual weight (including all fluids) for the lightest model/version of each horsepower listed in that grouping.

³ Variable Voltage Computer Controlled 133 Amp, Current Amp, calculated at 13.5 V. Net dedicated battery charging power output is 50 Amp.

⁴ On equipped models

⁵ Warranty: BRP 5 YEAR (STANDARD 3 + 2) EXTENDED LIMITED WARRANTY PROGRAMME. (Offered only through BRP European Distribution SA and its authorised BRP dealers for Evinrude® outboard engines that are sold to residents of the European Union for recreational use only). This Extended Limited Warranty Programme adds 24 months of BRP Limited Warranty coverage beyond the standard 36 month BRP Warranty (limited to 750 Hrs and 1000 Hrs on G2 Models whichever occurs first) applicable to Evinrude outboard engines under Special Conditions (see the Evinrude 2015 catalog for more details).