

9.8 HP

Engine Model (Color)	(a) E10R4 Blue (b) E10RL4 Blue (c) E10TEL4 Blue (d) E10EL4 Blue (e) E10TPL4 Blue (f) E10TPX4 Blue (g) E10PL4 Blue (h) E10PX4B Blue
Engine Type	2-cylinder
Bore x Stroke - mm (in)	2.17 x 1.73 (55 x 44)
Displacement - cc (cu in)	209 (12.8)
Gear Ratio	2.08:1
Full Throttle RPM Range	5000-6000 RPM
Weight in kg (lbs)*	(a)(b) 37 (81.5) (c)(d) 41 (90.4) (e) 46 (102.5) (f) 47 (104.5) (g) 47 (103.6) (h) 49 (107)
Starting	(a)(b) Rope (c)(d)(e)(f)(g)(h) Electric
Controls	(a)(b) Tiller Handle (c)(d)(e)(f)(g)(h) Mechanical
Fuel Induction	Carbureted
Alternator Output	Only on Electric Models: 12V, 145W, 6A (Standard on Electric Start Models)
Steering	(a)(b)(c)(e)(f) Tiller (d)(g)(h) Remote
Trim Method	Manual or Power Tilt
Shaft Length - mm (in)	(a) 381 (15) (b)(c)(d)(e)(g) 508 (20) (f)(h) 635 (25)
Recommended Fuel	87 Octane
Warranty	3-Year Warranty



* Dry weight for the lightest model/version of each engine listed in that grouping.

EVINRUDE®

